DH-P9X

12.1" Unattended Parking Intercom Pillar

One-Touch Help, Intelligent Management



Key Features

- One-Click Call/Help
- Automatic Call Cloud-based Agent
- 12.1" LCD Display
- QR Code Payment
- Remote Gate Opening/Closing
- High-Sensitivity Microphone
- Video Linkage with Multiple Screens
- Broadcasting and Speaking
- IP Network Architecture
- Parking Management Made Easy

Technical Specifications

Processor	High-performance Embedded SOC Processor	Card Swipe Interface	1 pc
Operating System (OS)	Embedded LINUX Operating System	Network	Wired/WiFi/4G
Sensor	1MP/1.3MP/2MP CMOS Sensor	Network Port	10/100M Adaptive Ethernet Port
Video Compression	H.264/25FPS	Ground Sensor/IO Interface	3 Channels Input
Audio Input	Built-in High-sensitivity Omnidirectional Microphone	Power Supply	AC 220V
Audio Output	Max. 20W	Power Consumption	≤30W
Compression Standard	G.711, G.713, GSM, DAC	Overall Dimensions	1350mm×230mm×90mm
Display	12.1-inch Industrial Display (-30°C~85°C)	Base Dimensions	310mm×170mm
Gate Open/Close Interface	1 Channel Gate Open Relay, 1 Channel Gate Close Relay	Material	Tempered Glass + Zinc-plated Steel Sheet
QR Code Interface	1 pc	Operating Temperature	-30°C~75°C

Applications



Parking Lots



Residential Communities



Commercial Complexes



Public Facilities



Smart Campuses