OUTDOOR VISUAL INTERCOM POINT

Blue Visual Intercom Alarm Post

Model **DH-B01Z**



01 Overview

Proactive visual safety monitoring for the last 100 meters

Designed for outdoor open spaces, it upgrades from passive waiting for alarms to proactive, visual safety monitoring points — distinct from indoor wall-mounted or small box-type alarm terminals.

SOS One-Click SOS	2WAY HD Two-Way Talk	CCTV 24H Video Surveillance
WARN Acoustic & Visual Warning	RED Dual-Link Redundancy	EXT Outdoor Open Space

Key Features

SHORT LIST

- ✓ One-click SOS with immediate alarm and accurate location tracking
- ✓ AI-enhanced HD two-way communication for loud and open spaces
- ✓ 24-hour HD video surveillance with full evidence collection
- ✓ Acoustic and visual warnings to deter dangerous actions early
- ✓ Dual-link redundancy for uninterrupted function under extreme conditions
- ✓ Alarm → location → visualization → response → documentation workflow

Specifications

Processor	High-performance embedded SOC processor	**Network Protocol**	SIP、TCP/IP、DNP
OS	Embedded Linux OS	**Network Port**	10/100M adaptive Ethernet port
Sensor	2MP CMOS sensor	**Alarm Interface**	3× Dry Contact Input, 2× Dry Contact Output
Network	4G / Wired	**Power**	POE/DC 12V 1A
Video Compression	H.264/25FPS	**Power Consumption**	10W
Audio Input	Built-in high-sensitivity omnidirectional microphone	**Material**	Brushed aluminum panel + zinc galvanized steel plate
Audio Output	Built-in 5W speaker + 30W amplifier output	**Dimensions**	200mm×200mm×2202mm
Audio Format	G.711、G.713、GSM、PCM	**Operating Temperature**	- 30°C~75°C
Audio Quality	Professional echo cancellation and noise suppression		